

**THE NETHERLANDS
(N E D E R L A N D)****COMMUNICATION**

Concerning⁽¹⁾:

- ~~approval granted~~
- ~~approval extended~~
- ~~approval refusal~~
- ~~approval withdrawn~~
- ~~production definitely discontinued~~

of a type of CNG component pursuant to Regulation number 110.

Approval number: E4-110R-000295

Extension number: 01

1. CNG component considered:

- ~~Container(s) or cylinder(s)~~⁽¹⁾
- ~~Pressure indicator~~
- ~~Pressure relief valve~~
- ~~Automatic valve(s)~~
- ~~Excess flow valve~~
- ~~Gas tight housing~~
- ~~Pressure regulator(s)~~
- ~~Non return valve(s)~~
- ~~Pressure relief device~~
- ~~Manual valve~~
- ~~Flexible fuel lines~~
- ~~Filling unit or receptacle~~
- Gas injector(s)
- Gas flow adjuster
- Gas/air mixer
- Electronic control unit
- Pressure and temperature sensor(s)
- CNG filter(s)



2. Trade name or mark : 30NA-FT10-XXXX
3. Manufacturer's name and address : Keihin Corporation
Shinjuku Normura Bldg. 39F
1-26-2 Nishi-Shinjuku-Ku
Tokyo 163-0539
Japan
4. If applicable, name and address of manufacturer's representative : NA
5. Submitted for approval on : February 2013
6. Technical service responsible for conducting approval tests : Kiwa Nederland B.V.
P.O. Box 137
7300 AC Apeldoorn
The Netherlands
7. Date of report issued by that service : 19-04-2013
8. Number of report issued by that service : 126155, 126703
9. Approval : ~~granted/refused/extended/withdrawn~~⁽¹⁾
10. Reason(s) of extension (if applicable) : The already homologated injector is extended with:
• Structures : Add two parts.
• Materials: Added parts (RING, BACK UP&CAP, VALVE SEAT) are the same as previous model .(KN8 30NA-FB60-2xxx)
Others are the same as exiting model.(KN9 30NA-FT10-2xxx)
• Shapes: Differ in Nozzle shape. But thickness has increased from the previous model.(KN9 30NA-FT10-2xxx)
11. Place : Zoetermeer
12. Date : 27-MAY-2013
13. Signature : 
14. The documents filed with the application or extension of approval can be obtained upon request.

⁽¹⁾ Strike out what does not apply.

ADDENDUM

1. Additional information concerning the type-approval of a type of CNG components pursuant to Regulation number 110.
 - 1.1. Container(s) or cylinder(s)
 - 1.1.1. Dimensions :
 - 1.1.2. Material :
 - 1.2. Pressure indicator
 - 1.2.1. Working pressure(s) ⁽²⁾ :
 - 1.2.2. Material :
 - 1.3. Pressure relief valve (discharge valve)
 - 1.3.1. Working pressure(s) ⁽²⁾ :
 - 1.3.2. Material :
 - 1.4. Automatic valve(s)
 - 1.4.1. Working pressure(s) ⁽²⁾ :
 - 1.4.2. Material :
 - 1.5. Excess flow valve
 - 1.5.1. Working pressure(s) ⁽²⁾ :
 - 1.5.2. Material :
 - 1.6. Gas-tight housing
 - 1.6.1. Working pressure(s) ⁽²⁾ :
 - 1.6.2. Material :
 - 1.7. Pressure regulator(s)
 - 1.7.1. Working pressure(s) ⁽²⁾ :
 - 1.7.2. Material :
 - 1.8. Check valve(s) or non-return valve(s)
 - 1.8.1. Working pressure(s) ⁽²⁾ :
 - 1.8.2. Material :
 - 1.9. Pressure relief device (temperature triggered)
 - 1.9.1. Working pressure(s) ⁽²⁾ :
 - 1.9.2. Material :
 - 1.10. Manual valve
 - 1.10.1. Working pressure(s) ⁽²⁾ :
 - 1.10.2. Material :
 - 1.11. Flexible fuel lines
 - 1.11.1. Working pressure(s) ⁽²⁾ :
 - 1.11.2. Material :
 - 1.12. Filling unit or receptacle
 - 1.12.1. Working pressure(s) ⁽²⁾ :
 - 1.12.2. Material :



- 1.13. Gas injector(s)
- 1.13.1. Working pressure(s) ⁽²⁾ : 450KPa
- 1.13.2. Material : Housing made out of stainless steel. Further details see report 126155, 126703

- 1.14. Gas flow adjuster
- 1.14.1. Working pressure(s) ⁽²⁾ :
- 1.14.2. Material :

- 1.15. Gas/air mixer
- 1.15.1. Working pressure(s) ⁽²⁾ :
- 1.15.2. Material :

- 1.16. Electronic control unit (CNG-fuelling)
- 1.16.1. Basic software principles :

- 1.17. Pressure and temperature sensor(s)
- 1.17.1. Working pressure(s) ⁽²⁾ :
- 1.17.2. Material :

- 1.18. CNG filter(s)
- 1.18.1. Working pressure(s) ⁽²⁾ :
- 1.18.2. Material :

⁽²⁾ Specify the tolerance

