



Installation manual Dedicated PART 2/2

MANUFACTURER	Ford
TYPE	B-Max (JK8)
ENGINE DISPLACEMENT	999
NUMBER OF VALVES	12
ENGINE CODE / NUMBER	SFJA / SFJB 74kW
VEHICLE CATEGORIES	M
TRANSMISSION	MT
VERSION	Direct LiquiMax-2.0
PETROL ECU MANUFACTURER / CODE	FoMoCo / BoschMotronic MED 17.0.1
HIGH PRESSURE PETROL POMP	Bosch 0261520094 / 0261520095
HIGH PRESSURE PETROL INJECTOR	FoMoCo
MODEL YEAR:	6-2012->
SYSTEM APPROVAL NUMBER (R115)	E4-115R-000009 / DLM-LPG 02
LOCATION SYSTEM STICKER	right side, centre door post
ENGINE SET NUMBER	347/070011/A
MANUAL NUMBER	076/0704300
DATE	2014-04-03

Copyright © Prins Autogassystemen B.V. 2012

Version 2012-11-02 D



TABLE OF CONTENTS

General instructions	2
Required equipment / tools / materials for installing a complete system	3
Vehicle check.....	3
Tightening moments.....	4
Direct LiquiMax	5
Overview Direct LiquiMax	6
Direct LiquiMax parts / approval numbers	7
DLM component location overview.....	8
Removal of the Bosch High Pressure Pump.....	9
Installation of the Bosch High Pressure Pump	10
Preparation	11
Preparation	12
Fuel Supply Unit / Fuel Return Unit	13
Pre-assembly Boostpump / FSU / FRU	14
Boost pump assy installation	15
Connection of the fuel hose to the boost pump	16
Mounting the adapted High pressure pump	17
Lpg / petrol fuel lines.....	18
Supply hose – Return hose – Tank wiring.....	19
Fuel lines	20
Mounting the AFC	21
Wiring routing.....	22
Wiring AFC / relay location.....	23
Mounting the fuel selection switch	24
Electrical connections.....	25
Petrol ECU.....	26
Electrical connections.....	27
Electrical connections.....	28
Electrical connections.....	29
Electrical connections.....	30
Checklist after installation.....	31

FOR EXPLANATION AND CIRCUIT DIAGRAMS SEE : INSTALLATION MANUAL GENERAL PART 1 / 2



General instructions

- The installation of the system shall be done in accordance with the installation manual provided by Prins Autogassystemen.
- This manual is based on Dutch regulations, always install the system in accordance to the local regulations.
- For an optimal functioning of the Direct LiquiMax system, maintain a clean and organized work environment during installation and maintenance to prevent pollution of the LPG components.
- Always download the "general manual 1/2 " from our website for basic instructions and diagrams.
- Always disconnect the battery when installing the lpg system. Make sure the ignition key is outside the car.
Be aware of central door locking, radio / telephone memory code, alarm system.
- Wear safety goggles when working on petrol filled system / connections (pressurized petrol)
- Do not place the main fuse into the fuse holder before having completed the installation of the system.
- The AFC has to be activated by means of the Prins diagnosis software.
- Never disconnect the AFC connector, unless you have removed the main fuse.
- When installing the wiring harness, ensure that it does not run near any of the ignition components.

Solder and insulate all electrical connections.

The wires in the loom are provided with numbers and text. The text on the wire explains the function of the wire.

The wire harness is not model specific, therefore it may be necessary to adjust the length of the wires.

Ensure maximum care is taken when connecting wiring.

Make professional joints using solder and shrink sleeve. Do not stretch the wiring harness.

- No component of the LPG-system shall be located within 100 mm of the exhaust or similar heat source, unless such components are adequately shielded against heat.
- If holes have to be drilled (wear safety glasses) for installing brackets, etc., the drilled holes must always be treated with an anti-corrosion agent, after the chips have been removed (especially when mounting a exterior filler into body work).
- After having completed the installation, check the whole system for lpg leakage; use a lpg leak detection device. Also check for leak of engine coolant, petrol and air.
- Fitting and maintenance is only allowed by Prins Autogassystemen selected LPG engineers.
- Failure to follow the instructions in this manual can result in a poor or non-working lpg installation or a dangerous situation.
- For maintenance instructions and filter registration see owner manual.
- Prins Autogassystemen is not responsible for any damages to people or objects as a result of changes to Prins products.
- Check our website regularly for diagrams, certificates, updates, info-bulletins and product information.

Register (warranty card) the system on the Prins warranty portal .



Required equipment / tools / materials for installing a complete system

- Complete workshop toolbox (wrenches, screwdrivers, cutters, pliers, ratchet, sockets)
- Car lift
- Portable computer : operating on Windows 98, W2000 or XP.
 - Internal memory : 16 Mb or more
 - Memory HD space : 5MB
 - Screen : 256 colours, advise colours 16 bits or more
 - Com port : 1 free COM port 1 or COM port 2 with a 9 or 25 pins connector
- Vehicle fuel system scan tool or OBD scan tool Prins (part nr. 099/99928)
- Exhaust gas analyser
- Multimeter
- Oscilloscope
- Prins diagnostic software
- Prins serial interface
- Torque wrench (10Nm)
- Torque wrench (200-250Nm)
- Portable light
- Assortment drill bits 4 to 12 mm
- Assortment cutters (ø 20, 30, 50, 70 mm)
- Portable drill or pneumatic drill
- Thread cutting device (male M6x1, M8x1, M10x1)
- Socket 46mm
- Air gun
- Vacuum cleaner
- Safety goggles
- Hot air gun
- Soldering iron, soldering tin
- Wire-stripping pliers
- Adhesive tape
- Adhesive sealant
- Thread locking compound
- Anti-corrosion agent / black body coating
- Gas leak detection device or foam leak spray
- Shrink sleeves

Vehicle check

- Check the vehicle drivability on petrol
- Check the fuel system for error codes (scan tool)
- Check if the catalytic converter is in good condition (exhaust gas analyzer)
- Check the condition of the ignition system (spark plugs, cables, coil)



Tightening moments

	Nm	SW
M 4 x 0,7	3.3	7
M 5 x 0,8	6.5	8
M 6 x 1,0	11.3	10
M 7 x 1,0	14.5	11
M 8 x 1	24.5	13
M 8 x 1,25	27.3	13
M 10 x 1	52	15-16-17
M 10 x 1,5	54	15-16-17
(filtered)Banjo bolt	10	14
Supply line connection	15	13
Fuel module Allen bolts	20	7
Filler hose connection	50	22

EXPLANATION OF SYMBOLS :




= IMPORTANT,
CAUTION



= WEAR SAFETY GOGGLES




Direct LiquiMax



Overview Direct LiquiMax

overview Direct Liqui Max




Direct LiquiMax parts / approval numbers

 1st generation  2nd generation	 1st generation  2nd generation
Fuel Supply Unit : E4-67R-010269	Fuel Return Unit : E4-67R-010270 Pressure Sensor : E4-67R-010051
	
Boost pump	High Pressure Pump : E4-67R-010266 High Pressure Rail : E4-67R-010267 High Pressure Injectors : E4-67R-010309
	 XD-3 LPG  XD-4 LPG
Prins ECU : E4-67R-010098 E4-10R-030507	Fuel lines series XD : E4-67R-010247 XD3 E4-67R-010247 XD4



DLM component location overview



Removal of the Bosch High Pressure Pump

-REMOVAL-


-WARNING-

In case of removing the high pressure fuel pump, high pressure fuel pipe, delivery pipe, there may be injury caused by leakage of the high pressure fuel.
Don't do any repair work right after engine stops (HOT engine).

- Turn the ignition switch OFF and disconnect the battery negative (-) cable.
- Wear safety goggles.
- Disconnect the fuel pressure regulator valve connector
- Disconnect the High Pressure fuel feed pipe (B)
- Remove the Low Pressure fuel pipe / hose (A).
- Remove the installation bolts (E), and then remove the high pressure fuel pump from the cylinder head assembly.

CAUTION:

Unscrew in turn the two bolts in small steps (0.5 turns). In case of fully unscrewing one of the two bolts with the other bolt installed, the housing surface of the cylinder head may break because of tension of the pump spring.



CAREFULLY store the removed petrol pump. Make sure no pollution can come into the pump.




Installation of the Bosch High Pressure Pump

INSTALLATION:

Before installing the high pressure fuel pump, position the roller tappet (**B&C**) in the lowest position by rotating the crankshaft. Otherwise the installation bolts may be broken because of tension of the pump spring.

Apply engine oil to the O-ring (**A**) of the high pressure fuel pump, the roller tappet (**B**), and the protrusion (**C**). (roller tappet, only if removed from cylinder head)
Also apply engine oil to the groove on the location where the protrusion (**C**) is installed.



Installation bolts:

When tightening the installation bolts of the high pressure fuel pump, tighten and turn the bolts in small step (0.5 turns) after tightening them with hand-screwed torque.

High pressure fuel pump installation bolt: 12.8 ~ 14.7 N.m

Fuel pipe:

First hand-tighten the nut(s) fully until they are not fastened any more in order to have them inserted in place and then completely tighten to the specified torque using a torque wrench.
If not tightening the bolts or nuts in a straight line with the mating bolt holes or fittings, it may cause a fuel leak due to broken threads.

High pressure fuel pipe installation nut: 26.5 ~ 32.4 N.m




Installation is reverse of removal.




Preparation







Remove the original petrol hose.



Preparation



Fuel Supply Unit / Fuel Return Unit




Black filtered banjo will only be used on inlet connections !

Filter inside sensor banjo



Pre-assembly Boostpump / FSU / FRU



See hose table for correct hoses



Boost pump assy installation





Connection of the fuel hose to the boost pump.

Connect the fuel supply hose to the boost pump.








Mounting the adapted High pressure pump




Lpg / petrol fuel lines

Hose		from	to	Length (cm)
1	XD-3	Adapter original petrol hose	Petrol boost pump	45
2	XD-3	Fuel supply unit	High pressure petrol pump	85
3	XD-3	Petrol boost pump	Fuel supply unit	20
4	XD-3	Fuel return unit	High pressure petrol pump	75






Install the fuel line using two bonded seal washers and banjo bolt :




Filtered banjo: (FSU supply inlets / boost pump inlet : black filtered banjo) :




Supply hose – Return hose – Tank wiring

Protect the supply- and return hose together with tank-wiring using the Ø16 split tube.
Mount the "hose assembly " with clamps, with a maximum distance of 40cm.



Fuel lines




Mounting the AFC



Wiring routing





Wiring AFC / relay location





Mount the switch.

Mounting the fuel selection switch



Backside eobd connector (2 torx screws)



Electrical connections

Check and measure the wiring in case of changes in the cars wiring colours.
Insulate not used wires.

Driver room


Wire number / code	Wire colour	Connection
3-pole micro connector 66 Ground fuel switch 3 +12V fuel switch 49 LIN fuel switch	Brown Red Yellow	Connect the 3-pole connector to the Prins fuel selection switch.
51 CAN-High	Blue-yellow	EOBD connector pin 20 white-blue
70 CAN-Low	Blue	EOBD connector pin 19 white

1-32 MAIN GND ecu MAIN GROUND SENSE MAIN GND pump driver MAIN GND boost pump	Brown	Connect to the '-' of the battery (-31) ; use a ring terminal. 
--	-------	--

4 – 13 – 44 +12V BATT sense +12V BATT fused +12V BATT boost pump +12V BATT pump driver	Red	Connect to the '+' of the battery (+30) ; use a ring terminal. Do not place the fuse in the holder before having completed the installation of the lpg system. 
--	-----	---



Petrol ECU



NOT USED WIRES:

17	Analog 2	Blue-black	insulate
10	Simulation 2	Green-black	insulate
115	Digital input 4	Yellow-red	insulate
117	Digital input 3	Yellow-black	insulate
97	Digital input 5	Yellow-orange	insulate
113	Digital input 6	Yellow-purple	insulate
6	Lambda1 WB	Orange	insulate
42	Lambda2 WB 10KΩ	Orange-white	insulate



Electrical connections

Check and measure the wiring in case of changes in the cars wiring colours.
Insulate not used wires.

B-connector

Wire number / code	Wire colour	Connection
18 Analog 1 25 Simulation 1	Blue-red Green-grey	High pressure petrol sensor signal interruption Sensor side. ECU side. Wire colour :blue-brown Wire location : ECU connector B, pin 38
19 Analog 4	Blue-white	High pressure petrol sensor ground Wire colour :grey-white Wire location : ECU connector B, pin 22
121 Wake-up	Red-grey	High pressure petrol sensor 5 Volt supply Wire colour : blue-white Wire location : ECU connector B, pin 7
27 +5V sensor 37 C ground 20 Analog 3 MAP* * When original sensor is used: cut off connector: Only use blue signal wire 20	Red:insulate Brown:insulate Blue	For measuring the inlet manifold pressure from the engine MAP sensor. Wire colour : blue-green Wire location : ECU connector B, pin 35
8 RPM	Purple-white	For measuring the engine speed signal. Wire colour : white-green Wire location : ECU connector B, pin 36
15 T-ect	Grey	For measuring the engine coolant temperature. Wire colour : yellow Wire location : ECU connector B, pin 23



Electrical connections

Check and measure the wiring in case of changes in the cars wiring colours.
Insulate not used wires.

A-connector

7	+12V IGNITION	Grey - white	Make a connection to ignition + / contact + (+15). Do not place the fuse in the holder before having completed the installation of the lpg system. Wire colour : purple-orange Wire location : ECU connector A, pin 48
119 23	Digital input 2 Digital Simulation	Yellow-grey Green-red	Digital Airflow signal (MAF) interruption Sensor side. ECU side. Wire colour :blue-brown Wire location : ECU connector A, pin 8



Electrical connections

**Check and measure the wiring in case of changes in the cars wiring colours.
Insulate not used wires.**

Engine room

Wire number / code	Wire colour	Connection
<i>3-pole connector</i>		Connect the 3-pole connector to the Psys sensor positioned into the Fuel Return Unit.
35 C Ground pin A	Brown	Sensor wire pin A
9 +5V sensor pin B	Red	Sensor wire pin B
16 Psys pin C	Green	Sensor wire pin C
14 T-LPG	Grey	Not used, insulate.
<i>2-pole connector Boost Pump</i>	Red	Connect the 2-pole connector to the lock-off valve of the Boost Pump.
106 + Lock-off Boost Pump	White-yellow	
98 Ground lock-off		
<i>2-pole connector FSU</i>	Red	Connect the 2-pole connector to the lock-off valve of the Fuel Supply Unit
108 + Lock-off FSU	Pink-yellow	
100 Ground lock off		
<i>2-pole connector FRU</i>	Red	Connect the 2-pole connector to the lock-off valve of the Fuel Return Unit
90 + Lock-off FRU	Blue-yellow	
82 Ground lock off		
<i>4-pole diagnose connector</i>		Diagnose connector for service / diagnosis
46 Service TxD	Grey	Connector pin 1
65 Service RxD	Grey	Connector pin 2
68 C ground	Brown	Connector pin 4
<i>Boost pump relay</i>		
107 + relay boost pump	Red	Pin 86 of the boost pump relay
99 GND relay boost pump	Green-yellow	Pin 85 of the boost pump relay
+12V fused BATT	Red	Pin 30 of the boost pump relay
+12V Boost pump	Red	Pin 87 of the boost pump relay
<i>Wiring tank pump driver relay</i>		
2 + driver relay	Red	Pin 86 of the driver relay
26 Ground driver relay	Green-yellow	Pin 85 of the driver relay
+12V BATT fused	Red 2.5mm ²	Pin 30 of the driver relay
+12V driver	Red 2.5mm ²	Pin 87 of the driver relay




Electrical connections

Check and measure the wiring in case of changes in the cars wiring colours.
Insulate not used wires.

Lpg tank housing

Wire number / code	Wire colour	Connection
3-pole tank level connector 40 Ground tank gauge 12 Tank level in 11 + tank level supply	Brown Blue Red	Connect the 3-pole connector to the tank level sensor.
1. 2-pole connector tank lock-off	Green-yellow Brown	From tank pump driver From tank pump driver
2. 3-pole connector tank pump	Red 2.5mm ² Brown 2.5mm ²	From tank pump driver From tank pump driver
3. 2-pole connector driver	Red 2.5mm ² Brown 2.5mm ²	From tank pump relay 87 From main ground
4. 2-pole connector driver	Green Grey	From AFC pin 22 pwm From AFC pin 64 diagnose



Checklist after installation

1. Install the system fuses.
Turn on ignition.
Connect the Prins interface wire and run the Prins diagnosis program.
When working on the car, beware of moving and rotating parts in the engine compartment (even when the engine is not running !!).
2. When commissioning the LPG system, you must activate the AFC with the diagnosis software.
3. Check whether the program in the AFC matches with the car (dedicated engine set):
See "Identification" in the diagnosis program.
4. Check all components and connections for any LPG leakage, use a LPG leak detector device or a fluid detection like soap. Also check for petrol leakage. Make sure the solenoid valves are in open position.
No evidence of leakage is permitted.
Caution for moving and rotating parts in the engine compartment !
5. Use the diagnosis software to check again all input and output signals.
6. Check the system for error codes and solve these, if required.
Check the petrol MMS for EOBD error codes.
Place the protection connector back on the diagnose connector.
7. Make a test drive and check the cars drivability on LPG and petrol.

